



HF200S CABLE AWP PT #2002025S



Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
2002025S	20AWG (26 x 0.16mm) Bare Copper	25	0.508	12.90	177

Recommended Applications:
 Continuous flexing, cable carrier, robotic flexing, automated material handling equipment and other flexing applications.

Basic Construction:
 Extra fine bare copper strands

Insulating Compound:
 Specially formulated TPE

Colour Code:
 Red with white number coding. Conductor count for three conductor cable and beyond includes a green/yellow ground conductor (minimum 30% coverage).

Shielding:
 Tinned copper braid 85% minimum coverage

Jacketing Compound:
 Specially formulated oil resistant black PVC

Minimum Bend Radius:
 7.5 x cable diameter in flexing applications
 3 x cable diameter in static applications

Temperature Range:
 For static applications -40C to +90C
 For flexing applications -5C to +90C

Nominal Voltage Rating:
 600V

Test Voltage:
 3000V

Approvals:
 90C, 600V, CSA, UL, AWM I/II, A/B, CE, pbf, FTI
 RoHS compliant
 Conforms to CE low voltage directive

1.888.668.3539 289.337.9500 flex@awpinc.com

