



HF210D High Flex Control Cable

ISO 9001
2008

HF210D CABLE AWP PT #2102418D



Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
2102418D	24AWG Class 6 Bare Copper	18	0.311	7.90	56

Recommended Applications:

Continuous flexing, cable carrier, robotic flexing, automated material handling equipment and other flexing applications.

Basic Construction:

Extra fine bare copper strands Class 6

Insulating Compound:

Specially formulated PVC

Colour Code:

DIN 47100

Jacketing Compound:

Specially formulated oil resistant PVC

Resistant to:

UV, oils, coolants, fuels, chemicals, water and abrasion

Suitable for extremely harsh environments

Minimum Bend Radius:

5 x cable diameter in flexing applications

3 x cable diameter in static applications

Temperature Range:

For static applications -40C to +90C

For flexing applications -5C to +90C

Nominal Voltage Rating:

300V

Test Voltage:

3000V

Approvals:

90C, 300V, CSA, UL, AWM I/II, A/B, CE, pbf, FT1

RoHS compliant

Conforms to CE low voltage directive

1.888.668.3539

289.337.9500

flex@awpinc.com

CABLE AS FLEXIBLE AS OUR PEOPLE